

D100 IP20 LED spotlight range Remote driver version



D100 IP20 Spotlight - Remote driver version

LED Spotlight with remote driver

The D100 spotlight range was developed for use in the relighting of Hereford Cathedral in conjunction with Light Perceptions.

Product description:

Each spotlight head - 10 Watt Citizen or Sharp COB


A wide variety of anti glare, beam control and colour filter accessories are available.

Various LED colour temperature and CRI options available


Fully lockable in both axes

Dimming options: 1 - 10V, DALI, DMX or phase

Satin black, satin white or any RAL colour finish



239 111 Provide driver enclosure







Product Code	IP	CRI	Colour Temp. (K)	Optics				Finish	Anti-glare snoot	
D100 REMOTE DRIVER	20	80 90	27=2,700k 30=3,000k 40=4,000k 45=4,500k 50=5,000k	Citizen:	20° 24° 29° 36° 42° 48°	Sharp:	17° 20° 29° 39° 45°	Black White Any RAL colour	Height (mm): Cut angle (°)	20mm -increments of 5 mm up to- 150mm 0° -increments of 5° up to- 75°

Radiant Architectural Lighting 10 Broadbent Close 20 - 22 Highgate High Street London N6 5JW ENGLAND UK T: + 44 (0) 20 8348 9003 F: + 44 (0) 20 8348 6478 E: david@radiantlights.co.uk www.radiantlights.co.uk Products and literature designed by DAVID MORGAN ASSOCIATES June 2016