

## Euclid 60 IP66 - RGBW or Tuneable White LEDs with colour-mixing lenses

LED linear lighting system IP66

## **Product description:**

The Euclid 60 RGBW system has been developed for use in exterior linear high output architectural lighting applications including wall grazing and wall washing

The system incorporates custom RGBW or Tuneable white Luzeon Z or CZ LED clusters with colour mixing Gaggione lenses

Available with 125mm or 100mm pitch between LED clusters. The system can be supplied in custom lengths based on either the 125mm or 100mm module length. Minimum 300 mm to maximum 2.5 mtrs

A range of Gaggione TIR colour-mixing lenses including elliptical distributions

Up to 60W per metre with 125mm pitch between LED clusters at 700mA drive current

230 V AC input with integral AC to DC drivers

Dimming options include Phase, 1- 10 V, DALI, DSI and DMX


Anti-glare accessories include a micro louvre, honeycomb louvre and custom snoots


Mounting brackets options include adjustable angle brackets or fixed angle brackets, as well as custom designs


Any RAL colour. 5 year warranty exterior grade powder coat


## Euclid 60 IP66 RGBW

High-power RGBW or tuneable white LEDs with colour-mixing lenses LED linear lighting system IP66










Custom combinations of different colour temp. white-light LEDs and different colour-light LEDs can be specified

White-light LEDs: Up to 5,000 Lumens per Mtr

RGBW LEDs: Up to 2,100 Lumens per Mtr)



Product Code	No. of LEDs per Mtr	IP	Length	LED Type	LED colour	Colour Temp. ( K)	CRI	Optics (°)	Anti-glare accessory	Bracket	Feed	Finish
EUCLID 60 IP66 RGBW L	80 LEDs per Mtr: 125 mm pitch between each cluster of 4x LEDs 100 LEDs per Mtr: 100mm pitch between each cluster of 4x LEDs	67	300mm -increments of 100mm or 125mm up to- 2,500mm	Cluster of 4 x LUXEON Z or CZ LEDs - RGBW or Tuneable white	Far Red, Red, Deep Red, Red-Orange, Amber, PC Amber, Mint, Lime, Green, Cyan, Blue, Royal Blue, Violet	22=2,200k 27=2,700k 30=3,000k 35=3,500k 40=4,000k 50=5,000k 57=5,700k 65=6,500k	70 80 90	LUXEON Z LEDs with Gaggione LLC25: E: 12.9+33.2° C: 16.8° N: 12.9° M: 20.8° W: 32.3° V: 55°	Honey-comb louvre Micro louvre Snoot: Specify height & cut-angle	Fixed angle Adjust- able angle Custom	End Back Side	Black White Any RAL- colour